

TRP-300R

30mil ENVIRONMENTAL GEOMEMBRANE LINER



TRP-300R is an excellent choice whether you are lining an irrigation pond, an industrial pond, water features in a common area, or a golf course water hazard. It is designed as a fish and plant safe liner also. TRP-300R environmental geomembrane is a HDPE/LDPE fabric designed for economical, safe containment of contaminated soils, liquids or sludge's. It is a perfect choice for storage of remediation/treatment of contaminated materials, fuels, chemicals, and water. Being a polyethylene product it has hydrocarbon, chemical and U.V. resistance. Its cold crack characteristics are excellent at -65°F (-54°C).

(Low Temperature – Hydrocarbon Stable)

BLACK TAPE, DUAL 14 x 14 (1500d) COUNT PER INCH

TESTED PROPERTY	TEST METHOD		UNIT ENGLISH (METRIC)	VALUE ENGLISH (METRIC)
Thickness			mil (mm)	30 ±10% (0.75)
Weight	ASTM D 1910		oz/yd ²	14.7 ± 5%
Coating Thickness			mils	8
Tensile Strength (Tongue Method)	ASTM D 751	Warp	lbs	560
		Weft	lbs	522
Elongation at Break	ASTM D 751	Warp	%	15
		Weft	%	18
Tear Strength (Tongue method)	ASTM D 751	Warp	lbs/in	120
		Weft	lbs/in	125
Bursting Strength (Mullen)	ASTM D 3786		psi	900
Bursting Strength (Ball)	ASTM D 3776		psi	680
Hydrostatic Resistance	ASTM D 751A		psi	340
Moisture Vapor Transmission	ASTM E 96 B		g/m ² /24 hrs	0.036
Low Temperature Cold Crack	ASTM D 2136		°F (°C)	-65 (-54)

This data is provided for informational purposes only. Titan makes no warranties as to the suitability or the fitness for a specific use or merchantability of the products referred to, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability from resulting loss or damage. This information is subject to change without notice, please check with us for current updates.

TITAN ENVIRONMENTAL USA

Tel: 1-713-849-1311 | Email: info@titanenviro.com | Web: www.titanenvirousa.com

(Rev. March, 2018)

TRUST. QUALITY. VALUE